

isobutene, liquefied, under pressure**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product name	: isobutene, liquefied, under pressure
Synonyms	: 1,1-dimethylethene; 1,1-dimethylethylene; 1,1-dimethylethylene, liquefied, under pressure; 1-propene, 2-methyl-; 2-methyl-1-propene; 2-methyl-1-propene, liquefied, under pressure; 2-methylpropene; 2-methylpropene, liquefied, under pressure; 2-methylpropylene; asym-dimethylethylene; asymmetrical-dimethylethylene, liquefied, under pressure; gamma-butylene; gamma-butylene, liquefied, under pressure; iso-butene; isobutene; isobutylene; isobutylene, liquefied petroleum gas; isopropylidenemethylene; methylpropene, liquified, under pressure; petroleumgas, liquefied, under pressure; propene, 2-methyl-
Registration number REACH	: 01-2119456616-32
Product type REACH	: Substance/mono-constituent
CAS number	: 115-11-7
EC index number	: 601-012-00-4
EC number	: 204-066-3
RTECS number	: UD0890000
Molecular mass	: 56.11 g/mol
Formula	: C4H8

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1 Relevant identified uses**

Industrial and professional use. Before use: carry out a risk assessment

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet**Supplier of the safety data sheet**

CHEMOGAS NV
Westvaardijk 85
B-1850 Grimbergen Belgium
☎ +32 2 251 60 87
✉ +32 2 252 17 51
info@chemogas.com

Distributor of the product

CHEMOGAS NV
Westvaardijk 85
B-1850 Grimbergen Belgium
☎ +32 2 251 60 87
✉ +32 2 252 17 51
info@chemogas.com

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Gas	category 1	H220: Extremely flammable gas.
Press. Gas	Liquefied gas	H280: Contains gas under pressure; may explode if heated.

2.2. Label elements

isobutene, liquefied, under pressure

**Signal word**

Danger

H-statements

H220

Extremely flammable gas.

H280

Contains gas under pressure; may explode if heated.

P-statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P381

Eliminate all ignition sources if safe to do so.

P377

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P410 + P403

Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

May build up electrostatic charges: risk of ignition

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

May cause frostbites

Slightly irritant to respiratory organs

Large spills/in enclosed spaces: risk of oxygen deficiency

Slightly irritant to eyes

Harmful to fishes

Harmful to invertebrates (Daphnia)

Harmful to algae

SECTION 3: Composition/information on ingredients

3.1. Substances

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
2-methylpropene 01-2119456616-32	115-11-7 204-066-3	C>99 %	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(10)	Mono-constituent

(1) For H-statements in full: see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

In case of frostbites: Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.

After eye contact:

Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Dizziness. Headache. Irritation of the respiratory tract. Ringing in the ears. Narcosis. Mental confusion. Excited/restless. Coordination disorders. Disturbances of consciousness. Increased salivation. Respiratory difficulties.

After skin contact:

Frostbites.

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

2 / 10

isobutene, liquefied, under pressure

After eye contact:

Redness of the eye tissue. EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the eye tissue.

After ingestion:

Not applicable.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media**5.1.1 Suitable extinguishing media:**

Water spray. Polyvalent foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO₂ are formed.

5.3. Advice for firefighters**5.3.1 Instructions:**

If no hazard for/from the surroundings: controlled burning. If hazardous substances are nearby: consider extinguishment. Extinguish only if gas supply/leak can be shut afterwards. Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Insulating gloves. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep upwind. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Avoid ingress of water in the containers.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Insulating gloves. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Tip the container on one side to stop the leakage. Try to reduce evaporation. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Prevent evaporation by covering with: sand, earth, vermiculite or powdered limestone. Shovel into closing drums. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities**7.2.1 Safe storage requirements:**

Storage temperature: <50 °C. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Store only in a stabilized state. Under a shelter/in the open. Detached building. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources, combustible materials, oxidizing agents, (strong) acids, halogens.

7.2.3 Suitable packaging material:

Steel, stainless steel, monel steel, aluminium, synthetic material, polyethylene, copper.

7.2.4 Non suitable packaging material:

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

3 / 10

isobutene, liquefied, under pressure

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Butène (tous isomères)	Time-weighted average exposure limit 8 h	250 ppm
	Time-weighted average exposure limit 8 h	583 mg/m ³

USA (TLV-ACGIH)

iso-Butene	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
------------	--	---------

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

isobutene, liquefied, under pressure

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	769 mg/m ³	
	Long-term local effects inhalation	1530 mg/m ³	

DNEL/DMEL - General population

isobutene, liquefied, under pressure

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	163 mg/m ³	
	Long-term local effects inhalation	918 mg/m ³	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Before use: check for peroxides and eliminate them. Measure the concentration in the air regularly. Measure the oxygen concentration in the air. Work under local exhaust/ventilation.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

High vapour/gas concentration: self-contained respirator.

b) Hand protection:

Insulated gloves.

- materials (good resistance)

Leather, nitrile rubber, polyethylene.

- materials (poor resistance)

Butyl rubber, natural rubber.

c) Eye protection:

Protective goggles.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquefied gas
Odour	Sweet odour
	Mild odour

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

4 / 10

isobutene, liquefied, under pressure

Odour threshold	46 mg/m ³
Colour	Colourless
Particle size	Not applicable (gas)
Explosion limits	1.8 - 9.6 vol % 37 - 235 g/m ³
Flammability	Extremely flammable gas.
Log Kow	2.11 - 2.34 ; Experimental value
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	-140 °C
Boiling point	-7 °C
Flash point	-80 °C
Evaporation rate	No data available
Relative vapour density	2
Vapour pressure	2560 hPa ; 20 °C 6100 hPa ; 50 °C
Solubility	water ; 263 mg/l ; 20 °C
Relative density	0.6 ; -7 °C
Decomposition temperature	No data available
Auto-ignition temperature	465 °C
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Specific conductivity	< 6000 pS/m
Critical temperature	144.7 °C
Critical pressure	40000 hPa
Surface tension	0.016 N/m
Absolute density	590 kg/m ³ ; -7 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Unstable on exposure to air.

10.3. Possibility of hazardous reactions

Reacts slowly on exposure to air: peroxidation resulting in increased fire or explosion risk. Polymerizes on exposure to some compounds. Violent to explosive reaction with many compounds e.g.: with (strong) oxidizers, with (some) halogens and with (some) acids.

10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

Combustible materials, oxidizing agents, (strong) acids, halogens.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

isobutene, liquefied, under pressure

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral						Data waiving	
Dermal						Data waiving	
Inhalation	LC50	OECD 403	> 23 mg/l	4 h	Rat (male/female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

isobutene, liquefied, under pressure

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

5 / 10

isobutene, liquefied, under pressure

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye						Data waiving	
Skin						Data waiving	

Conclusion

Not classified as irritating to the skin
 Not classified as irritating to the eyes
 Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

isobutene, liquefied, under pressure

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin						Data waiving	
Inhalation						Data waiving	

Conclusion

Not classified as sensitizing for skin
 Not classified as sensitizing for inhalation

Specific target organ toxicity

isobutene, liquefied, under pressure

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 407	146.6 mg/kg bw/day		No effect	28 day(s)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation (gases)	NOAEC	Equivalent to OECD 453	18359 mg/m ³ air		No effect	104 weeks (6h/day, 5 days/week)	Mouse (male/female)	Experimental value

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

isobutene, liquefied, under pressure

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Ames test	Bacteria (S.typhimurium)	No effect	Experimental value

Mutagenicity (in vivo)

isobutene, liquefied, under pressure

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474	2 days (6h/day)	Mouse (male)		Experimental value

Carcinogenicity

isobutene, liquefied, under pressure

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Organ	Effect
Inhalation (gases)	NOAEC	Equivalent to OECD 453	18.4 mg/l air	104 weeks (6h/day, 5 days/week)	Mouse (male/female)	Experimental value		No carcinogenic effect

Reproductive toxicity

isobutene, liquefied, under pressure

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	OECD 414	8000 ppm	17 days (gestation, daily)	Rat (male/female)	No effect		Experimental value
Maternal toxicity	NOAEC	OECD 414	8000 ppm	17 days (gestation, daily)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEC (P/F1)	OECD 422	18.4 mg/l		Rat (male/female)	No effect		Experimental value

Conclusion CMR

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

6 / 10

isobutene, liquefied, under pressure

Not classified for carcinogenicity
Not classified for mutagenic or genotoxic toxicity
Not classified for reprotoxic or developmental toxicity

Toxicity other effects

isobutene, liquefied, under pressure

No (test) data available

Chronic effects from short and long-term exposure

isobutene, liquefied, under pressure

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

isobutene, liquefied, under pressure

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		30.72 mg/l	96 h	Pimephales promelas			QSAR
Acute toxicity invertebrates	LC50		14 mg/l - 30 mg/l	48 h	Daphnia magna			QSAR
Toxicity algae and other aquatic plants	EC50		20.9 mg/l	72 h	Algae			QSAR

Conclusion

Harmful to fishes
Harmful to invertebrates (Daphnia)
Harmful to algae
Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

isobutene, liquefied, under pressure

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
	7.5 h	5E5 /cm ³	

Half-life soil (t1/2 soil)

Method	Value	Primary degradation/mineralisation	Value determination
Not applicable			

Conclusion

Readily biodegradable in water
Readily biodegradable in water in anaerobic conditions

12.3. Bioaccumulative potential

isobutene, liquefied, under pressure

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		7 - 19		Pisces	

Log Kow

Method	Remark	Value	Temperature	Value determination
		2.11 - 2.34		Experimental value

Conclusion

Low potential for bioaccumulation (BCF < 500)

12.4. Mobility in soil

Not applicable (gas)

12.5. Results of PBT and vPvB assessment

Substance does not meet the criteria of PBT, nor the criteria of vPvB according to Annex XIII of Regulation (EC) No 1907/2006, so is neither PBT nor vPvB.

12.6. Other adverse effects

isobutene, liquefied, under pressure

Global warming potential (GWP)

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

7 / 10

isobutene, liquefied, under pressure

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing dangerous substances).

Depending on branch of industry and production process, also other waste codes may be applicable. Hazardous waste according to Regulation (EU) No 1357/2014.

13.1.2 Disposal methods

Refer to manufacturer/supplier for information on recovery/ recycling. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1055
-----------	------

14.2. UN proper shipping name

Proper shipping name	Isobutylene
----------------------	-------------

14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	2F

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	662
Limited quantities	none.

Rail (RID)

14.1. UN number

UN number	1055
-----------	------

14.2. UN proper shipping name

Proper shipping name	Isobutylene
----------------------	-------------

14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	2F

14.4. Packing group

Packing group	
Labels	2.1 (+13)

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	662
Limited quantities	none.

Inland waterways (ADN)

14.1. UN number

UN number	1055
-----------	------

14.2. UN proper shipping name

Proper shipping name	Isobutylene
----------------------	-------------

14.3. Transport hazard class(es)

Class	2
Classification code	2F

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

8 / 10

isobutene, liquefied, under pressure

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	662
Limited quantities	none.

Sea (IMDG/IMSBC)

14.1. UN number

UN number	1055
-----------	------

14.2. UN proper shipping name

Proper shipping name	Isobutylene
----------------------	-------------

14.3. Transport hazard class(es)

Class	2.1
-------	-----

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Marine pollutant	-
Environmentally hazardous substance mark	no

14.6. Special precautions for user

Special provisions	
Limited quantities	none.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Annex II of MARPOL 73/78	Not applicable
--------------------------	----------------

Air (ICAO-TI/IATA-DGR)

14.1. UN number

UN number	1055
-----------	------

14.2. UN proper shipping name

Proper shipping name	Isobutylene
----------------------	-------------

14.3. Transport hazard class(es)

Class	2.1
-------	-----

14.4. Packing group

Packing group	
Labels	2.1

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	A1
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
100 %	

REACH Annex XVII - Restriction

Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
2-methylpropene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — “whoopee” cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs.2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

9 / 10

isobutene, liquefied, under pressure

placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
"For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation The Netherlands

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 06
Waterbezwaarlijkheid	9

National legislation Germany

WGK	nwg; Classification non-water polluting in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 1)
TA-Luft	5.2.5

National legislation France

No data available

National legislation Belgium

No data available

Other relevant data

TLV - Carcinogen	iso-Butene; A4
------------------	----------------

15.2. Chemical safety assessment

A chemical safety assessment has been performed.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

10 / 10