

ethylene oxide

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| | |
|---------------------------|-----------------------------------|
| Product name | : ethylene oxide |
| Synonyms | : ethene oxide; oxirane |
| Registration number REACH | : 01-2119432402-53 |
| Product type REACH | : Substance/mono-constituent |
| CAS number | : 75-21-8 |
| EC index number | : 603-023-00-X |
| EC number | : 200-849-9 |
| Molecular mass | : 44.05 g/mol |
| Formula | : C ₂ H ₄ O |

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Industrial use
Chemical raw material
Biocide

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

CHEMOGAS NV
Westvaartdijk 85
B-1850 Grimbergen Belgium
☎ +32 2 251 60 87
✉ +32 2 252 17 51
info@chemogas.com

Distributor of the product

CHEMOGAS NV
Westvaartdijk 85
B-1850 Grimbergen Belgium
☎ +32 2 251 60 87
✉ +32 2 252 17 51
info@chemogas.com

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

| Class | Category | Hazard statements |
|-----------------|---------------|--|
| Flam. Gas | category 1 | H220: Extremely flammable gas. |
| Press. Gas | Liquefied gas | H280: Contains gas under pressure; may explode if heated. |
| Chem. Unst. Gas | Category A | H230: May react explosively even in the absence of air. |
| Carc. | category 1B | H350: May cause cancer. |
| Muta. | category 1B | H340: May cause genetic defects. |
| Acute Tox. | category 3 | H331: Toxic if inhaled. |
| STOT RE | category 1 | H372: Causes damage to organs (central nervous system) through prolonged or repeated exposure. |
| Acute Tox. | category 4 | H302: Harmful if swallowed. |
| Skin Irrit. | category 2 | H315: Causes skin irritation. |
| Eye Irrit. | category 2 | H319: Causes serious eye irritation. |

ethylene oxide

| | | |
|---------|------------|---|
| STOT SE | category 3 | H335: May cause respiratory irritation. |
|---------|------------|---|

2.2. Label elements



Signal word

Danger

H-statements

| | |
|------|--|
| H220 | Extremely flammable gas. |
| H280 | Contains gas under pressure; may explode if heated. |
| H230 | May react explosively even in the absence of air. |
| H350 | May cause cancer. |
| H340 | May cause genetic defects. |
| H331 | Toxic if inhaled. |
| H302 | Harmful if swallowed. |
| H372 | Causes damage to organs (central nervous system) through prolonged or repeated exposure. |
| H335 | May cause respiratory irritation. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |

P-statements

| | |
|--------------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P280 | Wear protective gloves, protective clothing and eye protection/face protection. |
| P260 | Do not breathe gas. |
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

Supplemental information

Restricted to professional users.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard
 Odour threshold is well above the exposure limit
 Produces effects on the nervous system
 May cause frostbites
 Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

| Name REACH Registration No | CAS No EC No | Conc. (C) | Classification according to CLP | Note | Remark |
|------------------------------------|----------------------|-----------|--|---------------|------------------|
| ethylene oxide 01-2119432402-53 | 75-21-8 200-849-9 | >99.9 % | Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280 Chem. Unst. Gas A; H230 Carc. 1B; H350 Muta. 1B; H340 Acute Tox. 3; H331 STOT RE 1; H372 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 | (1)(2)(6)(10) | Mono-constituent |

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

2 / 14

ethylene oxide

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink.

After inhalation:

Remove the victim into fresh air. Immediately consult a doctor/medical service. Do not apply mouth-to-mouth resuscitation.

After skin contact:

Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists. In case of frostbites: Wash immediately with lots of water (15 minutes)/shower. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist.

After ingestion:

Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Central nervous system depression. Nausea. Vomiting. Headache. Dizziness. Disturbances of consciousness. EXPOSURE TO HIGH CONCENTRATIONS: Disturbances of heart rate. Respiratory difficulties. FOLLOWING SYMPTOMS MAY APPEAR LATER: Cramps/uncontrolled muscular contractions. Risk of lung oedema.

After skin contact:

Frostbites. Tingling/irritation of the skin. FOLLOWING SYMPTOMS MAY APPEAR LATER: Swelling of the skin. Red skin. Blisters. May stain the skin. AFTER CONTACT WITH WATER: Caustic burns/corrosion of the skin.

After eye contact:

Irritation of the eye tissue. Frostbites.

After ingestion:

Not applicable.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

5.1.2 Unsuitable extinguishing media:

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam.

Major fire: Water (water can be used to control jet flame), Foam.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. On heating: explosive decomposition. Polymerizes on exposure to temperature rise, on exposure to impurities, on exposure to light, on exposure to (some) metals and on exposure to (strong) acids/bases with heat release resulting in increased fire or explosion risk. Reacts slowly on exposure to water (moisture): heat release resulting in increased fire or explosion risk.

5.3. Advice for firefighters

5.3.1 Instructions:

If no hazard for/from the surroundings: controlled burning. If hazardous substances are nearby: consider extinguishment. Extinguish only if gas supply/leak can be shut afterwards. Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Insulating gloves. Head/neck protection. Protective clothing. Compressed air/oxygen apparatus.

ethylene oxide

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep upwind. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Protect substance against light. Avoid ingress of water in the containers.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Insulating gloves. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Tip the container on one side to stop the leakage. Try to reduce evaporation. Take account of toxic/corrosive precipitation water. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Prevent evaporation by covering with: foam. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Use earthed equipment. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Store in a dark area. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Unauthorized persons are not admitted. Under a shelter/in the open. Detached building. Keep only in the original container. Limited time of storage. May be stored under inert gas. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources, combustible materials, oxidizing agents, (strong) acids, (strong) bases, highly flammable materials, metals, halogens, alcohols, amines, water/moisture.

7.2.3 Suitable packaging material:

Stainless steel, carbon steel, polypropylene.

7.2.4 Non suitable packaging material:

Aluminium, iron, copper, tin.

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

| | | |
|------------------|--|-----------------------|
| Oxyde d'éthylène | Time-weighted average exposure limit 8 h | 1 ppm |
| | Time-weighted average exposure limit 8 h | 1.8 mg/m ³ |

The Netherlands

| | | |
|---------------|---|------------------------|
| Ethyleenoxide | Time-weighted average exposure limit 8 h (Public occupational exposure limit value) | 0.46 ppm |
| | Time-weighted average exposure limit 8 h (Public occupational exposure limit value) | 0.84 mg/m ³ |

France

| | | |
|------------------|--|-------|
| Oxyde d'éthylène | Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative) | 1 ppm |
|------------------|--|-------|

ethylene oxide

| | | |
|------------------|--|-------|
| Oxyde d'éthylène | Short time value (VL: Valeur non réglementaire indicative) | 5 ppm |
|------------------|--|-------|

UK

| | | |
|----------------|---|-----------------------|
| Ethylene oxide | Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) | 5 ppm |
| | Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) | 9.2 mg/m ³ |

USA (TLV-ACGIH)

| | | |
|----------------|--|-------|
| Ethylene oxide | Time-weighted average exposure limit 8 h (TLV - Adopted Value) | 1 ppm |
|----------------|--|-------|

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

| Product name | Test | Number |
|---|-------|--------|
| Ethylene oxide (organic and inorganic gases by Extractive FTIR) | NIOSH | 3800 |
| Ethylene Oxide (Qazi-Ketcham) | NON | 14 |
| Ethylene Oxide | NIOSH | 1614 |
| Ethylene Oxide | NIOSH | 3702 |
| Ethylene Oxide | OSHA | 1010 |
| Ethylene Oxide | OSHA | 30 |
| Ethylene Oxide | OSHA | 49 |
| Ethylene Oxide | OSHA | 50 |

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

ethylene oxide

| Effect level (DNEL/DMEL) | Type | Value | Remark |
|--------------------------|---------------------------------------|----------------------|--------|
| DMEL | Long-term systemic effects inhalation | 2 mg/m ³ | |
| DNEL | Acute systemic effects inhalation | 10 mg/m ³ | |

PNEC

ethylene oxide

| Compartments | Value | Remark |
|------------------------------|--------------------------|--------|
| Fresh water | 0.084 mg/l | |
| Marine water | 0.0084 mg/l | |
| Aqua (intermittent releases) | 0.84 mg/l | |
| STP | 13 mg/l | |
| Fresh water sediment | 0.329 mg/kg sediment dw | |
| Marine water sediment | 0.0329 mg/kg sediment dw | |
| Soil | 0.0165 mg/kg soil dw | |

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Use earthed equipment. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Work under local exhaust/ventilation. Exhaust gas must be neutralised.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Gas mask with filter type AX. Self-contained breathing apparatus if conc. in air > 5 ppm.

b) Hand protection:

Insulated gloves.

- materials (good resistance)

Butyl rubber.

- materials (less resistance)

Neoprene, natural rubber.

- materials (poor resistance)

Polyethylene, PVC, nitrile rubber, leather.

c) Eye protection:

Protective goggles.

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

5 / 14

ethylene oxide

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---------------------------|---|
| Physical form | Gas |
| Odour | Sweet odour Ether-like odour |
| Odour threshold | 257 - 690 ppm 470 - 1263 mg/m ³ |
| Colour | Colourless |
| Particle size | Not applicable (gas) |
| Explosion limits | 2.6 - 100 vol % 47 - 1820 g/m ³ |
| Flammability | Extremely flammable gas. |
| Log Kow | -0.3 ; 25 °C |
| Dynamic viscosity | 0.254 mPa.s ; 10 °C ; Liquid |
| Kinematic viscosity | Not determined |
| Melting point | -111 °C |
| Boiling point | 10.7 °C ; 1013 hPa |
| Flash point | Not applicable |
| Evaporation rate | Ether ; Not applicable 72 ; Butyl acetate |
| Relative vapour density | Not applicable |
| Vapour pressure | 1458 hPa ; 20 °C 3950 hPa ; 50 °C 1752 hPa ; 25 °C |
| Solubility | Water ; complete Ethanol ; complete Ether ; complete Acetone ; soluble |
| Relative density | 0.88 ; 10 °C ; Liquid |
| Decomposition temperature | >570 °C |
| Auto-ignition temperature | 429 °C |
| Explosive properties | No chemical group associated with explosive properties |
| Oxidising properties | No chemical group associated with oxidising properties |
| pH | 7 ; 10 % |

9.2. Other information

| | |
|-------------------------|-------------------------------|
| Minimum ignition energy | 0.065 mJ |
| Specific conductivity | 4 µS/m |
| Critical temperature | 196 °C |
| Critical pressure | 71900 hPa |
| Surface tension | 0.0267 N/m ; 10 °C ; 1000 g/l |
| Absolute density | 887 kg/m ³ ; 10 °C |

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Substance has neutral reaction.

10.2. Chemical stability

Unstable on exposure to heat. Unstable on exposure to light. Unstable on exposure to air.

10.3. Possibility of hazardous reactions

Reacts slowly on exposure to water (moisture): heat release resulting in increased fire or explosion risk. May react explosively even in the absence of air. Reacts violently with many compounds e.g.: with (strong) oxidizers: (increased) risk of fire/explosion. Prolonged storage: polymerizes slowly.

10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Use earthed equipment. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

6 / 14

ethylene oxide

10.5. Incompatible materials

Combustible materials, oxidizing agents, (strong) acids, (strong) bases, highly flammable materials, metals, halogens, alcohols, amines, water/moisture.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

ethylene oxide

| Route of exposure | Parameter | Method | Value | Exposure time | Species | Value determination | Remark |
|--------------------|-----------|--------|---------------|---------------|------------|---------------------|------------------|
| Oral | LD50 | Other | 330 mg/kg bw | | Rat (male) | Experimental value | Aqueous solution |
| Dermal | | | | | | Data waiving | |
| Inhalation (gases) | LC50 | Other | 2.63 mg/l air | 4 h | Rat (male) | Experimental value | |
| Inhalation (gases) | LC50 | Other | 1460 ppm | 4 h | Rat (male) | Experimental value | |

As the substance is a gas, inhalation is the most likely route of exposure

Conclusion

Harmful if swallowed.

Toxic if inhaled.

Corrosion/irritation

ethylene oxide

| Route of exposure | Result | Method | Exposure time | Time point | Species | Value determination | Remark |
|-------------------|------------|------------------------|------------------------|--------------|---------|---------------------|------------------|
| Eye | Irritating | Equivalent to OECD 405 | | 24; 48 hours | Rabbit | Experimental value | Aqueous solution |
| Skin | Irritating | | 1 minutes - 60 minutes | | Rabbit | Experimental value | Aqueous solution |
| Inhalation | Irritating | | | | | Annex VI | |

Insufficient data available. Classification according to Regulation (EC) No 1272/2008 - Annex VI

The liquid form can cause frostbites, typical for all liquefied gases

Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Specific target organ toxicity, single exposure: classified as irritant to respiratory organs

Respiratory or skin sensitisation

ethylene oxide

| Route of exposure | Result | Method | Exposure time | Observation time point | Species | Value determination | Remark |
|-------------------|--------|--------|---------------|------------------------|---------|---------------------|--------|
| Skin | | | | | | Data waiving | |

The study on skin sensitisation does not need to be conducted as the substance is a gas

Conclusion

Not classified as sensitizing for skin

No respiratory sensitization data available

Specific target organ toxicity

ethylene oxide

| Route of exposure | Parameter | Method | Value | Organ | Effect | Exposure time | Species | Value determination |
|----------------------|-----------|--------------------------|--------|------------------------|-----------|--|---------------------|---------------------|
| Dermal | | | | | | | | Data waiving |
| Inhalation (vapours) | NOAEC | Equivalent to OECD 453 | 10 ppm | Central nervous system | No effect | 104 weeks (6h/day, 5 days/week) | Rat (male/female) | Experimental value |
| Inhalation (vapours) | NOAEC | Subchronic toxicity test | 10 ppm | | No effect | 10 weeks (6h/day, 5 days/week) - 11 weeks (6h/day, 5 | Mouse (male/female) | Experimental value |

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

7 / 14

ethylene oxide

As the substance is a gas, inhalation is the most likely route of exposure

Conclusion

Causes damage to organs (central nervous system) through prolonged or repeated exposure.

Mutagenicity (in vitro)

ethylene oxide

| Result | Method | Test substrate | Effect | Value determination |
|---------------------------------------|------------------------|--|--------|---------------------|
| Positive without metabolic activation | Equivalent to OECD 471 | Bacteria (S.typhimurium) | | Experimental value |
| Positive without metabolic activation | Equivalent to OECD 476 | Chinese hamster lung fibroblasts (V79) | | Experimental value |

Mutagenicity (in vivo)

ethylene oxide

| Result | Method | Exposure time | Test substrate | Organ | Value determination |
|----------|--------|---------------|-------------------|-------|---------------------|
| Positive | Other | 4 h | Rat (male/female) | | Experimental value |

Conclusion

May cause genetic defects.

Carcinogenicity

ethylene oxide

| Route of exposure | Parameter | Method | Value | Exposure time | Species | Effect | Organ | Value determination |
|----------------------|-----------|------------------------|--------|---------------------------------|-------------------|-----------------------|-------|---------------------|
| Inhalation (vapours) | NOAEC | Equivalent to OECD 453 | 10 ppm | 104 weeks (6h/day, 5 days/week) | Rat (male/female) | No neoplastic effects | | Experimental value |

Conclusion

May cause cancer.

Reproductive toxicity

ethylene oxide

| | Parameter | Method | Value | Exposure time | Species | Effect | Organ | Value determination |
|------------------------|-----------|------------------------|----------------|--|-------------------|-----------|-------|---------------------|
| Developmental toxicity | NOAEC | Equivalent to OECD 414 | 0.18 mg/l air | 6 days (gestation, daily) - 15 days (gestation, daily) | Rat (female) | No effect | | Experimental value |
| Maternal toxicity | NOAEC | Equivalent to OECD 414 | 0.18 mg/l air | 6 days (gestation, daily) - 15 days (gestation, daily) | Rat (female) | No effect | | Experimental value |
| Effects on fertility | NOAEC (P) | Equivalent to OECD 415 | 0.054 mg/l air | 14 weeks (6h/day, 5 days/week) | Rat (male/female) | No effect | | Experimental value |

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

ethylene oxide

No (test)data available

Chronic effects from short and long-term exposure

ethylene oxide

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Red skin. Itching. Inflammation/damage of the eye tissue. Nausea. Vomiting. Sensorial disturbances. Headache. Impairment of the nervous system. Movement disturbances. Impairment of the blood forming system. Coordination disorders. Myasthenia. Change in the haemogramme/blood composition. Degeneration of heart tissue. Tumours of the gastrointestinal tract. Possible bladder tumours. Brain affection. Possible premature birth.

ethylene oxide

SECTION 12: Ecological information

12.1. Toxicity

ethylene oxide

| | Parameter | Method | Value | Duration | Species | Test design | Fresh/salt water | Value determination |
|---|-----------|------------------------|---------------------|-------------|---------------------------------|---------------|------------------|---------------------|
| Acute toxicity fishes | LC50 | EPA 660/3 - 75/009 | 84 mg/l | 96 h | Pimephales promelas | Static system | Fresh water | Experimental value |
| Acute toxicity crustacea | LC50 | EPA 600/3-75/009 | 137 mg/l - 300 mg/l | 48 h | Daphnia magna | Static system | Fresh water | Experimental value |
| Toxicity algae and other aquatic plants | EC50 | Equivalent to OECD 201 | 240 mg/l | 96 h | Pseudokirchneriella subcapitata | Static system | Fresh water | Experimental value |
| Toxicity aquatic micro-organisms | EC10 | OECD 209 | 130 mg/l | 180 minutes | | Static system | Fresh water | Experimental value |

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

ethylene oxide

Biodegradation water

| Method | Value | Duration | Value determination |
|-----------------------------------|-------------|-----------|---------------------|
| OECD 301C: Modified MITI Test (I) | 93 % - 98 % | 28 day(s) | Read-across |
| OECD 301D: Closed Bottle Test | 69 % | 20 day(s) | Experimental value |

Phototransformation air (DT50 air)

| Method | Value | Conc. OH-radicals | Value determination |
|---------------|-------------|-------------------------|---------------------|
| SRC AOP v1.92 | 57.2 day(s) | 500000 /cm ³ | QSAR |

Half-life soil (t1/2 soil)

| Method | Value | Primary degradation/mineralisation | Value determination |
|--------|----------------|------------------------------------|---------------------|
| | Not applicable | | |

Conclusion

Readily biodegradable in water

12.3. Bioaccumulative potential

ethylene oxide

Log Kow

| Method | Remark | Value | Temperature | Value determination |
|--------|--------|-------|-------------|---------------------|
| | | -0.3 | 25 °C | |

Conclusion

Not bioaccumulative

12.4. Mobility in soil

ethylene oxide

(log) Koc

| Parameter | Method | Value | Value determination |
|-----------|--------------------|-------|---------------------|
| log Koc | SRC PCKOCWIN v1.66 | 0.157 | QSAR |

Volatility (Henry's Law constant H)

| Value | Method | Temperature | Remark | Value determination |
|-------------------------------|--------------------|-------------|--------|---------------------|
| 12.159 Pa.m ³ /mol | SRC HENRYWIN v3.10 | 25 °C | | QSAR |

Percent distribution

| Method | Fraction air | Fraction biota | Fraction sediment | Fraction soil | Fraction water | Value determination |
|----------------|--------------|----------------|-------------------|---------------|----------------|---------------------|
| Mackay level I | 7.75 % | | 0 % | 0 % | 92.23 % | QSAR |

Conclusion

Low potential for adsorption in soil

12.5. Results of PBT and vPvB assessment

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

9 / 14

ethylene oxide

Substance does not meet the criteria of PBT, nor the criteria of vPvB according to Annex XIII of Regulation (EC) No 1907/2006, so is neither PBT nor vPvB.

12.6. Other adverse effects

ethylene oxide

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances).

Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Refer to manufacturer/supplier for information on recovery/ recycling. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

| | |
|-----------|------|
| UN number | 1040 |
|-----------|------|

14.2. UN proper shipping name

| | |
|----------------------|------------------------------|
| Proper shipping name | Ethylene oxide with nitrogen |
|----------------------|------------------------------|

14.3. Transport hazard class(es)

| | |
|------------------------------|-----|
| Hazard identification number | 263 |
| Class | 2 |
| Classification code | 2TF |

14.4. Packing group

| | |
|---------------|---------|
| Packing group | |
| Labels | 2.3+2.1 |

14.5. Environmental hazards

| | |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

14.6. Special precautions for user

| | |
|--------------------|-------|
| Special provisions | 342 |
| Limited quantities | none. |

Rail (RID)

14.1. UN number

| | |
|-----------|------|
| UN number | 1040 |
|-----------|------|

14.2. UN proper shipping name

| | |
|----------------------|------------------------------|
| Proper shipping name | Ethylene oxide with nitrogen |
|----------------------|------------------------------|

14.3. Transport hazard class(es)

| | |
|------------------------------|-----|
| Hazard identification number | 263 |
| Class | 2 |
| Classification code | 2TF |

14.4. Packing group

| | |
|---------------|---------------|
| Packing group | |
| Labels | 2.3+2.1 (+13) |

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

10 / 14

ethylene oxide

14.5. Environmental hazards

| | |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

14.6. Special precautions for user

| | |
|--------------------|-------|
| Special provisions | 342 |
| Limited quantities | none. |

Inland waterways (ADN)

14.1. UN number

| | |
|-----------|------|
| UN number | 1040 |
|-----------|------|

14.2. UN proper shipping name

| | |
|----------------------|------------------------------|
| Proper shipping name | Ethylene oxide with nitrogen |
|----------------------|------------------------------|

14.3. Transport hazard class(es)

| | |
|---------------------|-----|
| Class | 2 |
| Classification code | 2TF |

14.4. Packing group

| | |
|---------------|---------|
| Packing group | |
| Labels | 2.3+2.1 |

14.5. Environmental hazards

| | |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

14.6. Special precautions for user

| | |
|--------------------|-------|
| Special provisions | 342 |
| Limited quantities | none. |

Sea (IMDG/IMSBC)

14.1. UN number

| | |
|-----------|------|
| UN number | 1040 |
|-----------|------|

14.2. UN proper shipping name

| | |
|----------------------|------------------------------|
| Proper shipping name | ethylene oxide with nitrogen |
|----------------------|------------------------------|

14.3. Transport hazard class(es)

| | |
|-------|-----|
| Class | 2.3 |
|-------|-----|

14.4. Packing group

| | |
|---------------|-----------|
| Packing group | |
| Labels | 2.3 + 2.1 |

14.5. Environmental hazards

| | |
|--|----|
| Marine pollutant | - |
| Environmentally hazardous substance mark | no |

14.6. Special precautions for user

| | |
|--------------------|-------|
| Special provisions | 342 |
| Limited quantities | none. |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

| | |
|--------------------------|----------------|
| Annex II of MARPOL 73/78 | Not applicable |
|--------------------------|----------------|

Air (ICAO-TI/IATA-DGR)

14.1. UN number

| | |
|-----------|-----------|
| Transport | Forbidden |
| UN number | 1040 |

14.2. UN proper shipping name

| | |
|----------------------|------------------------------|
| Proper shipping name | Ethylene oxide with nitrogen |
|----------------------|------------------------------|

14.3. Transport hazard class(es)

| | |
|-------|-----|
| Class | 2.3 |
|-------|-----|

14.4. Packing group

| | |
|---------------|--|
| Packing group | |
| Labels | |

14.5. Environmental hazards

| | |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

14.6. Special precautions for user

| | |
|--|----|
| Special provisions | A2 |
| Limited quantities: maximum net quantity per packaging | |

ethylene oxide

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

| VOC content | Remark |
|-------------|--------|
| 100 % | |

REACH Annex XVII - Restriction

Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

| | Designation of the substance, of the group of substances or of the mixture | Conditions of restriction |
|----------------|---|--|
| ethylene oxide | Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as carcinogen category 1A or 1B (Table 3.1) or carcinogen category 1 or 2 (Table 3.2) and listed as follows: - Carcinogen category 1A (Table 3.1)/carcinogen category 1 (Table 3.2) listed in Appendix 1 - Carcinogen category 1B (Table 3.1)/carcinogen category 2 (Table 3.2) listed in Appendix 2 | Without prejudice to the other parts of this Annex the following shall apply to entries 28 to 30:1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant concentration specified in Directive 1999/45/EC where no specific concentration limit is set out in Part 3 of Annex VI to Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: "Restricted to professional users".2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Directive 1999/45/EC; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. |
| ethylene oxide | Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as germ cell mutagen category 1A or 1B (Table 3.1) or mutagen category 1 or 2 (Table 3.2) and listed as follows: - Mutagen category 1A (Table 3.1)/mutagen category 1 (Table 3.2) listed in Appendix 3 - Mutagen category 1B (Table 3.1) /mutagen category 2 (Table 3.2) listed in Appendix 4 | Without prejudice to the other parts of this Annex the following shall apply to entries 28 to 30:1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant concentration specified in Directive 1999/45/EC where no specific concentration limit is set out in Part 3 of Annex VI to Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: "Restricted to professional users".2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Directive 1999/45/EC; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. |
| ethylene oxide | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not. | 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopie" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs.2. Without prejudice to the application of other Community provisions on |

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Product number: 50538

Revision number: 0200

12 / 14

ethylene oxide

the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
 "For professional users only".3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation Belgium

| | |
|---------------------------|---|
| Additional classification | Oxyde d'éthylène; C; La mention "C" signifie que l'agent en question relève du champ d'application de l'arrêté royal du 2 décembre 1993 concernant la protection des travailleurs contre les risques liés à l'exposition à des agents cancérogènes et mutagènes au travail. |
|---------------------------|---|

National legislation The Netherlands

| | |
|--|--|
| Waterbezwaarlijkheid | Z (2) |
| SZW - Lijst van kankerverwekkende stoffen | Ethyleenoxide; Listed in SZW-list of carcinogenic substances |
| SZW - Lijst van mutagene stoffen | Ethyleenoxide; Listed in SZW-list of mutagenic substances |
| SZW - Lijst van voor de voortplanting giftige stoffen (vruchtbaarheid) | Ethyleenoxide; 1B; May damage fertility. |

National legislation France

| | |
|-----------------------|-----------------------|
| Catégorie cancérogène | Oxyde d'éthylène |
| Catégorie mutagène | Oxyde d'éthylène; M1B |

National legislation Germany

| | |
|---------|--|
| WGK | 3; Classification water polluting based on the R-phrases in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 3) |
| TA-Luft | 5.2.7.1.1; II |

National legislation United Kingdom

| | |
|------------|----------------------|
| Carcinogen | Ethylene oxide; Carc |
|------------|----------------------|

Other relevant data

| | |
|-----------------------|--------------------|
| IARC - classification | 1; Ethylene oxide |
| TLV - Carcinogen | Ethylene oxide; A2 |

15.2. Chemical safety assessment

A chemical safety assessment has been performed.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

- H220 Extremely flammable gas.
- H230 May react explosively even in the absence of air.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H372 Causes damage to organs (central nervous system) through prolonged or repeated exposure.

| | |
|--------------|--|
| (*) | INTERNAL CLASSIFICATION BY BIG |
| CLP (EU-GHS) | Classification, labelling and packaging (Globally Harmonised System in Europe) |
| DMEL | Derived Minimal Effect Level |
| DNEL | Derived No Effect Level |
| EC50 | Effect Concentration 50 % |
| ErC50 | EC50 in terms of reduction of growth rate |
| LC50 | Lethal Concentration 50 % |
| LD50 | Lethal Dose 50 % |
| NOAEL | No Observed Adverse Effect Level |
| NOEC | No Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |
| PBT | Persistent, Bioaccumulative & Toxic |
| PNEC | Predicted No Effect Concentration |

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

13 / 14

ethylene oxide

STP Sludge Treatment Process
vPvB very Persistent & very Bioaccumulative

Specific concentration limits CLP

| | | | |
|----------------|----------|--------------------------|---------------------------------|
| ethylene oxide | C ≥ 30 % | Chem. Unst. Cat. A; H230 | UN Manual of Tests and Criteria |
|----------------|----------|--------------------------|---------------------------------|

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: ATP8

Publication date: 2014-10-29

Date of revision: 2017-07-11

Reference number: 1400

Revision number: 0200

Product number: 50538

14 / 14